



Coilight™ & Coilight™ Reflector

Compact Fluorescent Lamp

USHIO Coilights™ have an ultra compact shape that allows for maximum axial and radial light distribution and less trapping and light absorption. This allows for true incandescent A-lamp replacement and more efficient reflector lamps.


Coilights are an energy efficient alternative to higher wattage incandescent lamps with up to 10 times more life.

FEATURES & BENEFITS


- Energy Efficient
- Long Life — Up to 10,000 Hours Average Life
- Low Mercury — Less than 2mg per Lamp
- 2700K & 4100K Color Temperatures
- Tri-phosphor Coating — High Color Rendering (80+ CRI)
- Integrated Electronic Ballast
- Same Light Profile as Incandescent Lamps
- Reflector Lamps for Area Lighting
- Universal Burn Position
- E26 & GU24 Base Types

USHIO Coilight™ & Coilight™ Reflector Series	Incandescent "A" Line Equivalent
13W.....	60W Incandescent
15W.....	65W Incandescent
18W.....	75W Incandescent
23W.....	75W Incandescent
26W.....	100W Incandescent


SPECIFICATIONS




**Coilight
GU24 Base**



**Coilight
E26 Base**



**PAR38
E26 Base**



**R30
E26 Base**

Watts (W)	Ordering Code	Lamp Description	Dimensions			Color Temp (K)	CRI	Approx Lumens (lm)	Burn Position	Average Rated Life*(h)	Commercial Life** (h)	Case Qty
			Dia (in)	MOL (mm)	MOL (in)							
COILIGHT™ GU24 Base												
13	3000545	CF13CLT/4100/GU24	1.8	86.36	3.4	4100	80+	800	Any	10000	12500	10
18	3000546	CF18CLT/2700/GU24	2.1	109.22	4.3	2700	80+	1200	Any	10000	12500	10
26	3000550	CF26CLT/2700/GU24	2.1	132.08	5.2	2700	80+	1610	Any	10000	12500	10
COILIGHT™ E26 Base (Not compliant with California Title 20.)												
13	3000443	CF13CLT/2700/E26	1.8	104.14	4.1	2700	80+	825	Any	10000	12500	10
23	3000157	CF23CLT/2700/E26	2.1	124.46	4.9	2700	80+	1600	Any	10000	12500	10
COILIGHT™ REFLECTOR PAR38 E26 Base (Not compliant with California Title 20.)												
23	3000559	CF23PAR38/2700/E26	4.8	127.00	5.0	2700	80+	1100	Any	10000	12500	12
COILIGHT™ REFLECTOR R30 E26 Base (Not compliant with California Title 20.)												
15	3000557	CF15R30/2700/E26	3.7	137.16	5.4	2700	80+	700	Any	10000	12500	12

* Based on ANSI / IESNA standards of 3 hours per start

** Based on estimated commercial operating standards of 12 hours per start

Discontinued - For Reference Only

Reliable operating temperatures 0° F to 120° F

Coilights are not designed for dimming circuits or photocells

Coilights are not to be used in fully enclosed fixtures without adequate ventilation

 contains mercury
contient du mercure

Manage in Accord with Disposal Laws
www.lamprecycle.org 1-800-895-8842



 **CALIFORNIA PROPOSITION 65 WARNING:** These products can expose you to Mercury known to the state of California to cause birth defects or other reproductive harm. For more information, please go to: www.p65warnings.ca.gov

USHIO