



Xenoline™ Miniature Xenon

Miniature Xenon Lamps

The USHIO Xenoline™ series consists of: Festoon, Rigid Loop and Wedge base miniature Xenon lamps. All Xenoline lamps are low voltage and have an extremely long life making these lamps ideal for track and strip lighting.

Available in:

- Festoon 3W, 5W, 10W
- Rigid Loop 5W, 10W
- Wedge Base ranging from 3W to 18W


FEATURES & BENEFITS

- Long Life - Up to 20,000 Hours Average Life
- UV Protected
- Low Pressure
- Less Heat
- Dimmable
- Compact Tubular Design


APPLICATIONS

- Accent Lighting
- Track Lighting
- Strip Lighting
- Landscape Lighting


SPECIFICATIONS



Festoon - S8.5/8 Base



Rigid Loop Base



Wedge Base

Watts (W)	Ordering Code	Lamp Description	Volts (V)	Bulb Shape	Bulb Finish	Lamp Current (A)	Dimensions		Color Temp (K)	Approx Lumens (lm)	Burn Position	Avg Rated Life (h)
Festoon - S8.5/8 Base							Dia (A)	MOL (B)	Case Quantity: 100			
3	5002234	FST 24V-3W/F/XX	24.0	T10	Frost	0.131	10.0	40.0	2600	30.0	Any	10000
5	5000765	FST 12V-5W/C/XX	12.0	T10	Clear	0.370	10.0	44.0	2600	50.0	Any	20000
5	5000886	FST 12V-5W/F/XX	12.0	T10	Frost	0.370	10.0	44.0	2600	50.0	Any	20000
5	5000766	FST 24V-5W/C/XX	24.0	T3	Clear	0.192	10.0	44.0	2600	50.0	Any	15000
5	5000755	FST 24V-5W/F/XX	24.0	T3	Frost	0.192	10.0	44.0	2600	50.0	Any	15000
10	5000850	FST 12V-10W/C/XX	12.0	T10	Clear	0.740	10.0	44.0	2650	120.0	Any	20000
10	5000891	FST 12V-10W/F/XX	12.0	T10	Frost	0.740	10.0	44.0	2650	120.0	Any	20000
10	5000851	FST 24V-10W/C/XX	24.0	T3	Clear	0.385	10.0	44.0	2500	120.0	Any	10000
10	5000756	FST 24V-10W/F/XX	24.0	T3	Frost	0.385	10.0	44.0	2500	120.0	Any	10000
Rigid Loop Base							Case Quantity: 50					
5	5000899	XRL 12V-5W/F/XX	12.0	T10	Frost	0.417	10.0	43.0	2500	45.0	Any	20000
5	5000854	XRL 24V-5W/C/XX	24.0	T3	Clear	0.208	10.0	43.0	2400	40.0	Any	20000
5	5000883	XRL 24V-5W/F/XX	24.0	T3	Frost	0.208	10.0	43.0	2400	40.0	Any	20000
10	5000853	XRL 12V-10W/C/XX	12.0	T10	Clear	0.833	10.0	43.0	2600	100.0	Any	20000
10	5000901	XRL 12V-10W/F/XX	12.0	T10	Frost	0.833	10.0	43.0	2600	100.0	Any	20000
10	5000855	XRL 24V-10W/C/XX	24.0	T3	Clear	0.417	10.0	43.0	2500	90.0	Any	20000
Wedge Base							Case Quantity: 10					
3.36	1001417	UWX-10122	14.0	T10	Clear	0.240	10.3	26.8	2600	15.0	Any	19000
5	1001598	UWX-1024S/LL	24.0	T3	Clear	0.208	10.3	26.8	2600	37.7	Any	10000
5	1002262	UWX-1024S/LL, Frosted	24.0	T10	Frost	0.208	10.3	26.8	2600	37.7	Any	10000
7.2	1003002	UWX-15	24.0	T5	Clear	0.300	15.0	37.8	2600	67.9	Any	2500
7.2	1003698	UWX-918	12.8	—	—	0.560	15.0	37.8	2600	82.0	—	10000
7.5	1002272	UWX-T10XEWB	24.0	T3	Clear	0.313	10.3	26.8	2600	65.3	Any	10000
10	1003038	UWX-15	24.0	T5	Clear	0.416	15.0	37.8	2600	126.0	Any	2000
11.5	1001430	UWX-15-1	12.0	T15	Clear	0.960	15.0	37.8	2600	120.0	Any	10000
18	1001433	UWX-15-5	12.0	T15	Clear	1.500	15.0	37.8	2600	250.0	Any	10000

All dimensions shown in millimeters unless otherwise noted.
Discontinued - For Reference Only

USHIO