



## Xenoline™ Miniature Xenon

### Miniature Xenon Lamps

The USHIO Xenoline™ series consists of: Festoon, Rigid Loop and Wedge base miniature Xenon lamps. All Xenoline lamps are low voltage and have an extremely long life making these lamps ideal for track and strip lighting.

Available in:

- Festoon 3W, 5W, 10W
- Rigid Loop 5W, 10W
- Wedge Base ranging from 3W to 18W


### FEATURES & BENEFITS

- Long Life - Up to 20,000 Hours Average Life
- UV Protected
- Low Pressure
- Less Heat
- Dimmable
- Compact Tubular Design


### APPLICATIONS

- Accent Lighting
- Track Lighting
- Strip Lighting
- Landscape Lighting


# SPECIFICATIONS



**Festoon - S8.5/8 Base**



**Rigid Loop Base**



**Wedge Base**

| Watts (W)             | Ordering Code | Lamp Description      | Volts (V) | Bulb Shape | Bulb Finish | Lamp Current (A) | Dimensions        |         | Color Temp (K)     | Approx Lumens (lm) | Burn Position | Avg Rated Life (h) |
|-----------------------|---------------|-----------------------|-----------|------------|-------------|------------------|-------------------|---------|--------------------|--------------------|---------------|--------------------|
| Festoon - S8.5/8 Base |               |                       |           |            |             |                  | Dia (A)           | MOL (B) | Case Quantity: 100 |                    |               |                    |
| 3                     | 5002234       | FST 24V-3W/F/XX       | 24.0      | T10        | Frost       | 0.131            | 10.0              | 40.0    | 2600               | 30.0               | Any           | 10000              |
| 5                     | 5000765       | FST 12V-5W/C/XX       | 12.0      | T10        | Clear       | 0.370            | 10.0              | 44.0    | 2600               | 50.0               | Any           | 20000              |
| 5                     | 5000886       | FST 12V-5W/F/XX       | 12.0      | T10        | Frost       | 0.370            | 10.0              | 44.0    | 2600               | 50.0               | Any           | 20000              |
| 5                     | 5000766       | FST 24V-5W/C/XX       | 24.0      | T3         | Clear       | 0.192            | 10.0              | 44.0    | 2600               | 50.0               | Any           | 15000              |
| 5                     | 5000755       | FST 24V-5W/F/XX       | 24.0      | T3         | Frost       | 0.192            | 10.0              | 44.0    | 2600               | 50.0               | Any           | 15000              |
| 10                    | 5000850       | FST 12V-10W/C/XX      | 12.0      | T10        | Clear       | 0.740            | 10.0              | 44.0    | 2650               | 120.0              | Any           | 20000              |
| 10                    | 5000891       | FST 12V-10W/F/XX      | 12.0      | T10        | Frost       | 0.740            | 10.0              | 44.0    | 2650               | 120.0              | Any           | 20000              |
| 10                    | 5000851       | FST 24V-10W/C/XX      | 24.0      | T3         | Clear       | 0.385            | 10.0              | 44.0    | 2500               | 120.0              | Any           | 10000              |
| 10                    | 5000756       | FST 24V-10W/F/XX      | 24.0      | T3         | Frost       | 0.385            | 10.0              | 44.0    | 2500               | 120.0              | Any           | 10000              |
| Rigid Loop Base       |               |                       |           |            |             |                  | Case Quantity: 50 |         |                    |                    |               |                    |
| 5                     | 5000899       | XRL 12V-5W/F/XX       | 12.0      | T10        | Frost       | 0.417            | 10.0              | 43.0    | 2500               | 45.0               | Any           | 20000              |
| 5                     | 5000854       | XRL 24V-5W/C/XX       | 24.0      | T3         | Clear       | 0.208            | 10.0              | 43.0    | 2400               | 40.0               | Any           | 20000              |
| 5                     | 5000883       | XRL 24V-5W/F/XX       | 24.0      | T3         | Frost       | 0.208            | 10.0              | 43.0    | 2400               | 40.0               | Any           | 20000              |
| 10                    | 5000853       | XRL 12V-10W/C/XX      | 12.0      | T10        | Clear       | 0.833            | 10.0              | 43.0    | 2600               | 100.0              | Any           | 20000              |
| 10                    | 5000901       | XRL 12V-10W/F/XX      | 12.0      | T10        | Frost       | 0.833            | 10.0              | 43.0    | 2600               | 100.0              | Any           | 20000              |
| 10                    | 5000855       | XRL 24V-10W/C/XX      | 24.0      | T3         | Clear       | 0.417            | 10.0              | 43.0    | 2500               | 90.0               | Any           | 20000              |
| Wedge Base            |               |                       |           |            |             |                  | Case Quantity: 10 |         |                    |                    |               |                    |
| 3.36                  | 1001417       | UWX-10122             | 14.0      | T10        | Clear       | 0.240            | 10.3              | 26.8    | 2600               | 15.0               | Any           | 19000              |
| 5                     | 1001598       | UWX-1024S/LL          | 24.0      | T3         | Clear       | 0.208            | 10.3              | 26.8    | 2600               | 37.7               | Any           | 10000              |
| 5                     | 1002262       | UWX-1024S/LL, Frosted | 24.0      | T10        | Frost       | 0.208            | 10.3              | 26.8    | 2600               | 37.7               | Any           | 10000              |
| 7.2                   | 1003002       | UWX-15                | 24.0      | T5         | Clear       | 0.300            | 15.0              | 37.8    | 2600               | 67.9               | Any           | 2500               |
| 7.2                   | 1003698       | UWX-918               | 12.8      | —          | —           | 0.560            | 15.0              | 37.8    | 2600               | 82.0               | —             | 10000              |
| 7.5                   | 1002272       | UWX-T10XEWB           | 24.0      | T3         | Clear       | 0.313            | 10.3              | 26.8    | 2600               | 65.3               | Any           | 10000              |
| 10                    | 1003038       | UWX-15                | 24.0      | T5         | Clear       | 0.416            | 15.0              | 37.8    | 2600               | 126.0              | Any           | 2000               |
| 11.5                  | 1001430       | UWX-15-1              | 12.0      | T15        | Clear       | 0.960            | 15.0              | 37.8    | 2600               | 120.0              | Any           | 10000              |
| 18                    | 1001433       | UWX-15-5              | 12.0      | T15        | Clear       | 1.500            | 15.0              | 37.8    | 2600               | 250.0              | Any           | 10000              |

All dimensions shown in millimeters unless otherwise noted.  
Discontinued - For Reference Only

# USHIO