

Catalog Number: _____ Type: _____

Project: _____

Comments: _____ Date: _____

Halco Linear Strip Retrofit Series



Halco's Linear Strip Retrofit Series are the ideal solution to convert outdated lighting into energy-efficient LED fixtures in a matter of minutes. One can expect immediate cost savings thru ease of installation, reduced maintenance costs, and up to 50% cut in energy consumption. Each retrofit includes all one needs for seamless installation. The products are designed to universally fit most 4.25" and 5.25" T8/T12 fluorescent wide strips. The diffused lens promotes aesthetically pleasing light output with minimal glare.

Performance

- Replaces pre-existing 4' and 8' fluorescent strip fixtures
- Driver efficiency >85%
- CRI >80
- L70 Lumen Maintenance > 60,000 hours
- 5 year limited warranty
- 0-10V Dimming Standard, dimmable down to 10%
- Universal 120-277VAC

Construction

- Universal design fits most 4.25" and 5.25" T8/T12 Fluorescent housing
- 2 of the 4' Units combine with easy-to-use bracket to make 8' unit
- Intergal LED gear tray and reflector
- Driver on board
- Diffused lens that requires no additional frame or fastener

Certification

- UL Listed
- ROHS Compliant
- DLC Premium
- Damp Location

Applications

- Commercial
- Industrial
- Retail
- Storage/Utility
- Shops
- Task Lighting

Ordering Information Table

Model Selection					
Family	Size	/	Wattage	Voltage	CCT
LSRK=Linear Strip Retrofit Kit	4=4 foot 8=8 foot		36=36 Watts 72=72 Watts	U=120-277VAC	40=4000K 50=5000K

Halco Linear Strip Retrofit Series

Product Information Table

Product Code	Product Number	Product Description	Weight
LSRK4/36U40	10247	LINEAR STRIP RETROFIT KIT 4 FT: 36 WATTS, 120-277V, 4000K	5.75
LSRK4/36U50	10248	LINEAR STRIP RETROFIT KIT 4 FT: 36 WATTS, 120-277V, 5000K	5.75
LSRK8/72U40	10250	LINEAR STRIP RETROFIT KIT 8 FT: 72 WATTS, 120-277V, 4000K	12.12
LSRK8/72U50	10251	LINEAR STRIP RETROFIT KIT 8 FT: 72 WATTS, 120-277V, 5000K	12.12

Product Specification Table

Rated Wattage	36	72
Input Voltage	120-277VAC	
Power Factor	> 0.9	
L70 Lifetime*	>50,000	
Efficacy	>130LPW	
Total Harmonic Distortion (THD)	<20%	
CRI	>80, R9 >0	
Dimming	0-10V Continuous Dimming	
CCT	4000K, 5000K	
Warranty	5 Years Standard	
Color Consistency	5-Step MacAdam Ellipse	
Wet	Damp Location, 20-85% RH, non-condensing	
DLC	-20°C to 50°C	
Weight (lbs)	5.75	12.12

Energy Savings Table

Halco Retrofit	Comparable Fluorescent	LED Advantage
4' 36W	2 x 32W T8	50% Less Watts
8' 72W	2 x 59W T8	38% Less Watts

Performance Data Table

Product	Rated Wattage	4000K		5000K	
		Delivered Lumens	Efficacy	Delivered Lumens	Efficacy
LSRK4/36UXX	36	4896	136	4906	136
LSRK8/72UXX	72	9792	136	9812	136

Quick ship: 4000K and 5000K. Other CCTs may require a lead time or be special order



2 Typical color consistency. May vary or be changed.

3 L70 hours calculated based on LED package manufacturer LM80 report and ISTMT report of LED in luminaire. Stated values are for select catalog numbers. Contact manufacturer for detailed information

Halco Linear Strip Retrofit Series

Photometrics


LSK4/36U50




ZONAL LUMEN SUMMARY			
ZONE	LUMENS	% LAMP	% LUMINAIRE
0-30	940.9	21%	21%
0-40	1,562.8	34.9%	34.9%
0-60	2,873.5	64.1%	64.1%
60-90	1,277.4	28.5%	28.5%
70-100	915.1	20.4%	20.4%
90-120	319.6	7.1%	7.1%
0-90	4,150.8	92.6%	92.6%
90-180	331.8	7.4%	7.4%
0-180	4,482.6	100%	100%

LUMENS PER ZONE					
ZONE LUMENS%		TOTAL	ZONE LUMENS%		TOTAL
	112.7	2.5%		190.0	4.2%
10-20	325.7	7.3%	100-110	96.6	2.2%
20-30	502.5	11.2%	110-120	33.0	0.7%
30-40	621.8	13.9%	120-130	5.6	0.1%
40-50	669.1	14.9%	130-140	1.9	0%
50-60	641.6	14.3%	140-150	1.8	0%
60-70	552.3	12.3%	150-160	1.5	0%
70-80	426.4	9.5%	160-170	1.0	0%
80-90	298.6	6.7%	170-180	0.4	0%

Dimensions



4' LSRK4/36U40 / LSRK4/36U50



8' LSRK8/72U40 / LSRK8/72U50