



LED LAMPS

ProLED Linear T8 Direct Series



Easy To Install



50,000 Hours



Direct Ballast
Compatible



Food Equipment
Certification



DLC Qualified

The easiest way to replace fluorescent T8 and achieve over 50% energy savings and longer life without the need for any new tools or rewiring



2 Foot, 3 Foot, 4 Foot Options

No Re-Wiring Necessary

Instant On - No Flicker

Backed by a 5-Year Warranty

Applications:

- Office
- Education
- Food Service
- High Bay Luminaires
- Hospitality
- Medical
- Retail

Markets:

- Commercial
- Industrial



Contact Your Customer Care Specialist
For Pricing, Orders And Technical Support.

800.677.3334 www.halcolighting.com


ProLED[®]

Linear T8 Direct Series


Product #: _____ Type: _____
 Project: _____ Date: _____
 Comments: _____ Initials: _____

Specifications

- Operates on instant start, programmed start ballasts and emergency ballasts
- 50,000 hour life resulting in lower maintenance costs over time
- Uses 48% less energy and lasts up to 73% longer resulting in lower costs for the end user¹
- Suitable for use in totally enclosed luminaires
- Conforms to requirements of NSF/ANSI standard 2-food equipment
- UL listed for damp locations
- Dimmable (48" only)



Savings Comparison



[†] Maintenance costs based on 15 minutes at \$40 per/hr
[‡] Energy costs based on \$0.11 kWh

Ordering Information



Lamp Wattage	System Wattage [§]	Base	Product #	Product Code	Color Temp.	CRI	Lumens	Useful Life*	Dimmable	Beam Spread	Pkg. Qty.	MOL	THD	DLC [®] Code	DLC [®] Qualified	Equivalent Wattage	
8	10	G13	84068	T824FR8/835/DIR2/LED	3500K	82	1250	50,000	No	270°	25	24"	<20%	PX7JB5ZH	Yes	17	
8	10	G13	84069	T824FR8/840/DIR2/LED	4000K	82	1250	50,000	No	270°	25	24"	<20%	P5J2JPHJ	Yes	17	
8	10	G13	84070	T824FR8/850/DIR2/LED	5000K	82	1250	50,000	No	270°	25	24"	<20%	P4Z7M453	Yes	17	
10	13	G13	83171	T836FR10/835/DIR/LED	3500K	82	1400	50,000	No	270°	25	36"	<20%	PL3W1BACWT58	Yes	25	
10	13	G13	83172	T836FR10/840/DIR/LED	4000K	82	1400	50,000	No	270°	25	36"	<20%	PL9BMANKBV12	Yes	25	
10	13	G13	83173	T836FR10/850/DIR/LED	5000K	82	1400	50,000	No	270°	25	36"	<20%	PLRWW1KTWG1E	Yes	25	
⊗	12	15	G13	83880	T8FR12/835/DIR4/LED	3500K	82	1800	50,000	Yes	270°	25	48"	<20%	PLPR40VDQWEI	Yes	32
⊗	12	15	G13	83881	T8FR12/840/DIR4/LED	4000K	82	1850	50,000	Yes	270°	25	48"	<20%	PL6VY9G73MQL	Yes	32
⊗	12	15	G13	83882	T8FR12/850/DIR4/LED	5000K	82	1850	50,000	Yes	270°	25	48"	<20%	PL13J2GK2NIP	Yes	32

For full listing of ballast compatibility see halcolighting.com

⊗ NEW ITEM

* Useful Life is defined as the point in time at which the lamp will maintain at least 70% of its initial lumens. The lamp will continue to burn past this point, but at decreased light levels.

Warranty – Commercial / Industrial: This product is warranted for 5 years from the date of purchase.

Must be operated with an ambient fixture temperature between -4°F(-20°C) and 122°F(50°C).

[§] Energy savings based on \$0.11 kWh over a 50,000 hour life.

** Check the latest update at www.DesignLights.org for listed product catalog numbers. Not all versions are listed.