



T8

14.5T8/COR/48-835/MF20/G 10/1

Philips MainsFit (UL Type B) CorePro T8 LED tubes deliver high-quality, flicker free performance at an affordable price. The UL Type B LED tubes are designed with easy installation and long-term maintenance simplicity in mind. Upgrade your lighting to Philips and realize 50,000 hour LED lifetime backed by a 5-year, full replacement limited warranty. The DLC 5.1 listed products are compatible with Philips new PTB15D emergency driver meeting UL 924 requirements.

Product data

General information	
Base	G13 [Medium Bi-Pin Fluorescent]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	50000 h
Switching Cycle	50000
Technical Type	14.5-32W
Light technical	
Color Code	835 [CCT of 3500K]
Beam Angle (Nom)	240 °
Initial lumen (Nom)	2000 lm
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3500 K
Luminous Efficacy (rated) (Nom)	137.00 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and electrical	
Input Frequency	50 to 60 Hz
Power (Rated) (Nom)	14.5 W

Lamp Current (Max)	124 mA
Lamp Current (Min)	58 mA
Wattage Equivalent	32 W
Starting Time (Nom)	0.5 s
Warm Up Time to 60% Light (Nom)	0.5 s
UL Type	Type B - bypass the ballast
Power Factor (Nom)	0.9
Voltage (Nom)	120-277 V
Temperature	
T-Ambient (Max)	113 °F
T-Ambient (Min)	-4 °F
T-Storage (Max)	149 °F
T-Storage (Min)	-40 °F
T-Case Maximum (Nom)	158 °F
Controls and dimming	
Dimmable	Limited
Mechanical and housing	
Bulb Finish	Frosted

T8

Bulb Material	Glass
Product Length	48 in
Bulb Shape	Tube, double-ended

Approval and application


Energy Saving Product	Yes
Approbation Marks	DLC compliance
Approbation Marks	RoHS compliance UL certificate
Energy Consumption kWh/1000 h	- kWh

Product data

Order product name	14.5T8/COR/48-835/MF20/G 10/1
--------------------	-------------------------------

EAN/UPC - Product	046677563530
Order code	563536
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929002484504
Net Weight (Piece)	0.474 lb
Model Number	9290024845


Dimensional drawing




14.5T8/COR/48-835/MF20/G 10/1

Product	D1	D2	A1	A2	A3
14.5T8/COR/48-835/MF20/G 10/1	1-1/16 in	1-1/8 in	47-3/16 in	47-1/2 in	47-3/4 in

Photometric data




LEDtube COR 14,5W G13 2000lm 835





LEDtube COR 9,9W G13 1550lm 835

Photometric data





LEDtube COR 9,9W G13 1550lm

Lifetime



Life Expectancy Diagram

LEDtube 50K FailureRate-LED




LEDtube COR 9,9W 50K LumenVsTc

Lumen Maintenance Diagram

T8

Lifetime



LEDtube 50K LifetimeVsTc-LED

