



# Tuff Guard High CRI T8 Lamps

## F32T8/TL935/ALTO TG 30PK

Tuff Guard T8 lamps are designed to contain shattered glass particles in case of accidental breakage. Coated lighting is essential to help ensure the welfare of your customers, employees, and operation.

### Warnings and Safety

- The lamps must be installed and operating in ambient temperatures below 120°F.
- The lamps cannot be used in fixtures employing defective ballasts, ballasts that have been used longer than their rated life or ballasts that are improperly wired.
- The lamps cannot be used in fixtures where poor pin contact occurs.
- Lamp types and ballast types must be compatible (rapid start lamps with rapid start ballast, etc.).
- Lamps are recommended for open fixtures.


### Product data

General information		Wattage Equivalent		32 W
Base	G13 [ Medium Bi-Pin Fluorescent]	Voltage (Nom)	137 V	
Main Application	General Lighting (G)	<b>Mechanical and housing</b>		
Features	ALTO® (ALTO)	Bulb Finish	Coated glass	
<b>Light technical</b>		Cap-Base Information	Green Base	
Color Code	935 [ CCT of 3500K]	Nominal Length (Inch)	48	
Beam Angle (Nom)	0 °	Bulb Shape	T8 [ T8 (T8)]	
Luminous Flux (Rated) (Nom)	2625 lm	<b>Approval and application</b>		
Correlated Color Temperature (Nom)	3500 K	Mercury (Hg) Content (Nom)	1.7 mg	
Color Rendering Index (Nom)	>90	<b>Product data</b>		
<b>Operating and electrical</b>		Order product name	F32T8/TL935/ALTO TG 30PK	
Lamp Current (Nom)	265 mA			

## Tuff Guard High CRI T8 Lamps


EAN/UPC - Product	046677536497
Order code	536490
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	30
Material Nr. (12NC)	927871204905

Net Weight (Piece)	0.002 lb
--------------------	----------



### Dimensional drawing

Product
F32T8/TL935/ALTO TG 30PK



F32T8/TL935/ALTO TG 30PK

