



ProLume.

< Programmed Start T5

ProLume® Programmed Start T5

Halco
LIGHTING TECHNOLOGIES

Energy Efficient

- Delivers up to 104 LPW with a compact design
- Improved tri-phosphor coating provides superior color rendering - up to 86 CRI
- Excellent lumen maintenance - up to 94%

Technical Data

- Low profile
- Minimum starting temperature -15°F
- Peak operating temperature 95°F
- Uniform surface brightness regardless of length
- Special coating on glass wall prevents glass and phosphor mercury absorption
- 3000, 3500, 4100, and 5000K

Benefits Over Standard T8 or T12 Lamps

- Delivers superior optical control
- All T5 lamps have the same surface brightness for uniform lighting
- Higher peak operating temperatures, 95°F vs. 77°F for T8 and T12 lamps
- 2-Year Guarantee

Applications

- Cove lighting
- Display lighting
- Indirect fixtures
- High-bay fixtures

The Eco-Shield®
mark indicates
this product is
TCLP compliant.



Call Halco today and get
a great look at our vast
product line, personal
service and fast delivery.
Visit us at halcolighting.com.

Your account representative
is your single source
for pricing, orders, and
technical support.

Shipping from Atlanta,
Cleveland, Houston,
and Phoenix.

ISO 9001 Certified



**where there's light,
there's halco®**

(800) 677-3334

halcolighting.com

Bulb Type	Watts	Base	Product #	Product Code	Description	Pkg/ Qty	Color Temp	CRI	Initial Lumens	Mean Lumens	Avg Rated Life	Commercial Life**	Nom Length (in)
PROGRAMMED START ECO-SHIELD®													
T5	14	G5	30117	F14T5/830/ECO/IC	830 Phosphor Eco-Shield®	25	3000	86	1350	1270	24000	30000	22"
T5	14	G5	30118	F14T5/835/ECO/IC	835 Phosphor Eco-Shield®	25	3500	86	1350	1270	24000	30000	22"
T5	14	G5	30119	F14T5/841/ECO/IC	841 Phosphor Eco-Shield®	25	4100	86	1350	1270	24000	30000	22"
T5	21	G5	30125	F21T5/830/ECO/IC	830 Phosphor Eco-Shield®	25	3000	86	2100	1990	24000	30000	34"
T5	21	G5	30126	F21T5/835/ECO/IC	835 Phosphor Eco-Shield®	25	3500	86	2100	1990	24000	30000	34"
T5	21	G5	30127	F21T5/841/ECO/IC	841 Phosphor Eco-Shield®	25	4100	86	2100	1990	24000	30000	34"
T5	24	G5	30134	F24T5/835/HO/ECO/IC	835 Phosphor High Output Eco-Shield®	25	3500	86	2000	1900	24000	30000	22"
T5	24	G5	30135	F24T5/841/HO/ECO/IC	841 Phosphor High Output Eco-Shield®	25	4100	86	2000	1900	24000	30000	22"
T5	35	G5	35049	F35T5/835/ECO/IC	835 Phosphor Eco-Shield®	25	3500	86	3650	3450	24000	30000	58"
T5	35	G5	35050	F35T5/841/ECO/IC	841 Phosphor Eco-Shield®	25	4100	86	3650	3450	24000	30000	58"
T5	37	G5	35060	F39T5/830/HO/ECO/IC	830 Phosphor High Output Eco-Shield®	25	3000	86	3500	3320	24000	30000	34"
T5	37	G5	35061	F39T5/835/HO/ECO/IC	835 Phosphor High Output Eco-Shield®	25	3500	86	3500	3320	24000	30000	34"
T5	37	G5	35062	F39T5/841/HO/ECO/IC	841 Phosphor High Output Eco-Shield®	25	4100	86	3500	3320	24000	30000	34"
T5	28	G5	35041	F28T5/830/ECO/IC	830 Phosphor Eco-Shield®	25	3000	86	2900	2750	24000	30000	46"
T5	28	G5	35042	F28T5/835/ECO/IC	835 Phosphor Eco-Shield®	25	3500	86	2900	2750	24000	30000	46"
T5	28	G5	35043	F28T5/841/ECO/IC	841 Phosphor Eco-Shield®	25	4100	86	2900	2750	24000	30000	46"
T5	28	G5	35044	F28T5/850/ECO/IC	850 Phosphor Eco-Shield®	25	5000	86	2900	2750	24000	30000	46"
☼ T5	49	G5	35085	F49T5/835/HO/ECO	835 Phosphor High Output Eco-Shield®	25	3500	86	4900	4700	24000	30000	46"
☼ T5	49	G5	35088	F49T5/841/HO/ECO	841 Phosphor High Output Eco-Shield®	25	4100	86	4900	4700	24000	30000	46"
☼ T5	49	G5	35089	F49T5/850/HO/ECO	850 Phosphor High Output Eco-Shield®	25	5000	86	4900	4700	24000	30000	46"
T5	54	G5	35081	F54T5/830/HO/ECO/IC	830 Phosphor High Output Eco-Shield®	25	3000	86	5000	4850	24000	30000	46"
T5	54	G5	35082	F54T5/835/HO/ECO/IC	835 Phosphor High Output Eco-Shield®	25	3500	86	5000	4850	24000	30000	46"
T5	54	G5	35083	F54T5/841/HO/ECO/IC	841 Phosphor High Output Eco-Shield®	25	4100	86	5000	4850	24000	30000	46"
T5	54	G5	35084	F54T5/850/HO/ECO/IC	850 Phosphor High Output Eco-Shield®	25	5000	86	5000	4850	24000	30000	46"
☼ T5	54	G5	35086	F54T5/865/HO/ECO/IC	865 Phosphor High Output Eco-Shield®	25	6500	86	5000	4850	24000	30000	46"
☼ T5	80	G5	35087	F80T5/835/HO/ECO	835 Phosphor High Output Eco-Shield®	25	3500	86	7000	6650	24000	30000	57.1"
☼ T5	80	G5	35090	F80T5/841/HO/ECO	841 Phosphor High Output Eco-Shield®	25	4100	86	7000	6650	24000	30000	57.1"
ULTRA EFFICIENT T5 EXTENDED LIFE													
T5	28	G5	35046	F28T5/835/ECO/XL	835 Phosphor Eco-Shield®	25	3500	86	2800	2660	40000	46000	46"
T5	28	G5	35047	F28T5/841/ECO/XL	841 Phosphor Eco-Shield®	25	4100	86	2800	2660	40000	46000	46"
T5 HIGH OUTPUT EXTENDED LIFE													
T5	54	G5	35070	F54T5/835/HO/ECO/XL	835 Phosphor Eco-Shield®	25	3500	86	5000	4790	40000	46000	46"
T5	54	G5	35071	F54T5/841/HO/ECO/XL	841 Phosphor Eco-Shield®	25	4100	86	5000	4790	40000	46000	46"
T5	54	G5	35072	F54T5/850/HO/ECO/XL	850 Phosphor Eco-Shield®	25	5000	86	5000	4790	40000	46000	46"
CIRCLINE PROGRAMMED START 2GX13													
T5	22	2GX13	109080	FC22T5/835	835 Phosphor	20	3500	82	1900	1800	10000	12500	9"
T5	22	2GX13	109082	FC22T5/841	841 Phosphor	20	4100	82	1900	1800	10000	12500	9"
T5	40	2GX13	109084	FC40T5/835	835 Phosphor	20	3500	82	3350	3150	10000	12500	12"
T5	40	2GX13	109086	FC40T5/841	841 Phosphor	20	4100	82	3350	3150	10000	12500	12"

☼ NEW ITEM!

** Based on commercial standards of 12 hours per start.

☼ Hg—LAMP CONTAINS MERCURY, MANAGE IN ACCORD WITH DISPOSAL LAWS.

Visit www.lamprecycle.org for disposal information for your state or local government.