



MSR Gold™ FastFit

MSR Gold™ 2000/2 FastFit 1CT/8

All lamps burn out eventually, but when this happens with single ended MSR Gold™ FastFit, it is replaced in seconds – thanks to the specially designed lamp base and lamp holder. This lamp provides a high beam intensity of pure, white light for a truly illuminating performance, while the gold-plated caps provide superior heat protection and prevent premature failure. P3 technology allows use in any position and at higher temperatures, further extending lamp life and consistency of high-quality light output. Also, because the FastFit design is applied to Philips Halogen lamps, switching between lamp technologies can be done quickly and easily. The Philips MSR Gold™ 2000/2 FastFit can be operated in a lamp wattage range between 800W and 1400W.

Product data

GeniPubl	
PGJX50 PGJX50	PGJX50 [PGJX50]
Universal Universal	Universal [Universal]
Entertainment	Entertainment
750 h	750 h
FastFit	FastFit
LittPubl	
2	2
138000 lm	138000 lm
160000 lm	160000 lm
297	297
322	322
7500 K	7500 K
80 lm/W	80 lm/W
88	88

ElecPubl	
2000 W	2000 W
15.4 A	15.4 A
198 V	198 V
CntrPubl	
Yes	Yes
MechPubl	
PGJX50	PGJX50
LDRPubl	
950 °C	950 °C
500 °C	500 °C
ProductPubl	
MSR Gold™ 2000/2 FastFit 1CT/8	MSR Gold™ 2000/2 FastFit 1CT/8


MSR Gold™ FastFit

8727900908305	8727900908305
245605	245605
1	1
8	8

928106105114	928106105114
0.147 kg	0.147 kg

Warnings and Safety

Dimensional drawing



Product	D (max)	O	L (min)	L (max)	L	C (max)	F
MSR Gold™ 2000/2 FastFit 1CT/8	34 mm	8.0 mm	66 mm	68 mm	67 mm	134 mm	50 mm

MSR GOLD 2000/2 FastFit

