

## 64788 CP/72 FTM 240V



### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable to 0% with traditional amber shift

### Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

## Technical data

### General product information

|                       |                                                                         |
|-----------------------|-------------------------------------------------------------------------|
| Product Number        | 54485                                                                   |
| Product Name          | 64788CP72FTM240V 12/CS 1/SKU                                            |
| Ordering Abbreviation | 64788 CP/72 FTM 240V                                                    |
| Brand Name            | OSRAM                                                                   |
| General Description   | 64788, CP/72, FTM, 2000W, 240V, GY16 base, Tungsten halogen, Single-end |

### Electrical data

|                 |        |
|-----------------|--------|
| Nominal Wattage | 2000 W |
| Nominal Voltage | 240 V  |

### Light technical data

|                                |          |
|--------------------------------|----------|
| Luminous Flux                  | 52000 lm |
| Light Center Length - LCL (in) | 2.76 in  |
| Light Center Length - LCL (mm) | 70 mm    |
| Color Temperature              | 3200 K   |
| Color Rendering Index          | 100      |
| Average Rated Life             | 400 h    |


### Physical attributes

|                   |          |
|-------------------|----------|
| Base              | GY16     |
| Bulb Shape        | T10      |
| Length l (in)     | 5.71 in  |
| Length l (mm)     | 145 mm   |
| Diameter d (in)   | 1.339 in |
| Diameter d (mm)   | 34.00 mm |
| Distance a (in)   | 2.760 in |
| Distance a (mm)   | 70 mm    |
| Reflector Coating | 34.00    |

### Additional product data

|                    |            |
|--------------------|------------|
| Operating Position | s90        |
| Cooling            | CONVECTION |

Product datasheet



Packaging Information

| Product number | EAN/UPC       | Packaging           | Quantity | Outside dimensions l x w x h | Gross weight |
|----------------|---------------|---------------------|----------|------------------------------|--------------|
| 54485          | 4008321632180 | Folding box (SKU)   | 1        | 2.8 in x 2.8 in x 6.3 in     | 0.2 lb       |
| 54485          | 4008321984272 | Shipping box (Case) | 12       | 11.6 in x 8.7 in x 6.9 in    | 3.4 lb       |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.