



# MasterConnect

## 8T8/24-850/IF12/MAScon IA 10/1

Philips MasterConnect LEDtube InstantFit T8, which is Interact Ready, enables an easy upgrade to a connected lighting system without re-wiring the fixtures. The 2.4GHz mesh networking technology allows wireless integration with a variety of control devices, such as sensor and switch, for easy light automation. It also offers secure and reliable communication towards the Interact IoT platform or verified third party systems. The result? Greater energy savings, various control possibilities and a more adaptable space!

### Product data


General Information	
Base	G13 [ Medium Bi-Pin Fluorescent]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	50000 h
Switching Cycle	50000X
Light Technical	
Color Code	850 [ CCT of 5000K]
Beam Angle (Nom)	160 °
Initial lumen (Nom)	1200 lm
Correlated Color Temperature (Nom)	5000 K
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Input Frequency	40000-85000 Hz
Power (Rated) (Nom)	8 W
Lamp Current (Max)	280 mA
Lamp Current (Min)	70 mA

Starting Time (Nom)	0.5 s
Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.9
Voltage (Nom)	200-380 V
Temperature	
T-Ambient (Max)	45 °C
T-Ambient (Min)	-20 °C
T-Storage (Max)	65 °C
T-Storage (Min)	-40 °C
T-Case Maximum (Nom)	35 °C
Controls and Dimming	
Dimmable	Wireless Dim
Mechanical and Housing	
Product Length	600 mm
Approval and Application	
Energy Saving Product	Yes

Approbation Marks	UL certificate RoHS compliance DLC compliance
Energy Certifications	DLC Standard
<b>Product Data</b>	
Order product name	8T8/24-850/IF12/MAScon IA 10/1
EAN/UPC - Product	046677537289
Order code	537282

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001398764
Net Weight (Piece)	0.080 kg
Model Number	9290013987



## Dimensional drawing



TLED SMART 2ft HF 8-18W 1050lm 5000K


Product	D1	D2	A1	A2	A3
8T8/24-850/IF12/MAScon IA 10/1	25.6 mm	27.8 mm	588.6 mm	595.7 mm	602.8 mm

## Photometric data





LEDtube 8W G13 850 160D IF EasySmart

LEDtube 8W G13 830 160D IF EasySmart





LEDtube 8W G13 850 160D IF EasySmart

Lifetime




LEDtube 15W G13 830-850 160D IF 6U EasySmart

LEDtube 15W G13 830-850 160D IF 6U EasySmart



LEDtube 15W G13 830-850 160D IF 6U EasySmart

LEDtube 15W G13 830-850 160D IF 6U EasySmart



LEDtube 15W G13 830-850 160D IF 6U EasySmart

