



# Double Ended Linear

## Double Ended Linear BC300T3Q/CL/TP 120V 6/2PK

High-quality white light with superior lumen performance. Halogen Double Ended lamps provide bright, white light for work lights and security lighting. Rugged construction for busy work sites. Offered in several lengths to meet most application needs. High lumen output provides light where you need it.

### Product data

General Information		Approval and Application	
Base	R7S [ R7s]	Energy Efficiency Label (EEL)	E
Operating Position	Horizontal +/- 4 D [ Horizontal +/- 4 D]	Luminaire Design Requirements	
Nominal Lifetime (Nom)	2000 h	Bulb Temperature (Max)	900 °C
Light Technical		Pinch Temperature (Max)	350 °C
Initial lumen (Nom)	5000 lm	Product Data	
Correlated Color Temperature (Nom)	2900 K	Order product name	Double Ended Linear BC300T3Q/CL/TP 120V 6/2PK
Luminous Efficacy (rated) (Nom)	16 lm/W	EAN/UPC - Product	50046677415711
Color Rendering Index (Nom)	100	Order code	415711
Operating and Electrical		Numerator - Quantity Per Pack	1
Power (Rated) (Nom)	300 W	Numerator - Packs per outer box	6
Lamp Current (Nom)	2.5 A	Material Nr. (12NC)	924884936301
Starting Time (Nom)	0.0 s	Net Weight (Piece)	0.010 kg
Voltage (Nom)	120 V	Controls and Dimming	
Controls and Dimming		Dimmable	Yes
Mechanical and Housing		Mechanical and Housing	
Bulb Finish	Clear		

## Double Ended Linear

### Dimensional drawing



Product	D (max)	B (max)	B	B (min)	C (max)
Double Ended Linear BC300T3Q/CL/TP 120V 6/2PK	12 mm	115.8 mm	114.2 mm	112.6 mm	117.6 mm

DESmall 300W R7s 120V T3 CL

