



# Halogen Low Voltage

## ELC/10H 6 250W 24V 24PK

The long lifetime of most of the Halogen Low Voltage lamps is further extended by the unique P3 technology developed by Philips. This allows the lamp to be used at higher temperatures, thereby extending the lamp's lifetime, reducing early failures, and resulting in fewer maintenance man hour costs. P3 also ensures consistency of high-quality light output, and allows the lamp to be used in any burning position, which enables more compact fixture designs. In addition, the compact filament produces a clean white light and high beam intensity for true natural colors on stage and without any hotspots.

### Product data


| General Information         |                        |
|-----------------------------|------------------------|
| Base                        | GX5.3 [ GX5.3]         |
| Philips Code                | 13163                  |
| ANSI Code                   | ELC-10H                |
| LIF Code                    | A1/259-10H             |
| Operating Position          | Universal [ Universal] |
| Main Application            | Disco/Theatre          |
| Life to 50% Failures (Nom)  | 1000 h                 |
| Light Technical             |                        |
| Color Rendering Index (Nom) | 100                    |
| Operating and Electrical    |                        |
| Power (Rated) (Nom)         | 250 W                  |
| Voltage (Nom)               | 24 V                   |
| Controls and Dimming        |                        |
| Dimmable                    | Yes                    |

| Mechanical and Housing          |                               |
|---------------------------------|-------------------------------|
| Bulb Material                   | Quartz-UV Open                |
| Reflector Finish                | Smooth                        |
| Filament Dimensions WxH         | -                             |
| Luminaire Design Requirements   |                               |
| Bulb Temperature (Max)          | 900 °C                        |
| Pinch Temperature (Max)         | 400 °C                        |
| Working Distance WD             | 31.7 mm                       |
| Product Data                    |                               |
| Order product name              | ELC/10H 250W GX5.3 24V 1CT/24 |
| EAN/UPC - Product               | 8711500436863                 |
| Order code                      | 136580                        |
| Numerator - Quantity Per Pack   | 1                             |
| Numerator - Packs per outer box | 24                            |
| Material Nr. (12NC)             | 924913220540                  |
| Net Weight (Piece)              | 0.024 kg                      |

## Halogen Low Voltage

---

### Dimensional drawing



#### Product

ELC/10H 250W GX5.3 24V 1CT/24

13163 ELC/10H 250W GX5.3 24V

