



T8

14T8/48-3000 IF 10/1 ROT

Our TLEDs are available in InstantFit (Type A / Type C) or MainsFit (Ballast bypass / Type B) versions. The InstantFit lamps work on a broad variety of ballasts and LED drivers. Only InstantFit has over 15,000 lamp & ballast combinations delivering even light output, energy savings and a long lifetime. Our MainsFit products feature a double-ended design, simplifying installation while a proprietary safety circuit minimizes a shock risk. Lamp sizes range from 2-foot to 8-foot and U-bend with a variety of lumen outputs.

Product data


General Information		Starting Time (Nom)		0.5 s
Base	G13 [Medium Bi-Pin Fluorescent]	Warm Up Time to 60% Light (Nom)		0.5 s
EU RoHS compliant	Yes	UL Type		Type A - works on ballast
Nominal Lifetime (Nom)	50000 h	Power Factor (Nom)		0.9
Switching Cycle	50000X	Voltage (Nom)		120-277, 347 V
Light Technical		Temperature		
Color Code	830 [CCT of 3000K]	T-Ambient (Max)		45 °C
Beam Angle (Nom)	180 °	T-Ambient (Min)		-20 °C
Initial lumen (Nom)	2000 lm	T-Storage (Max)		65 °C
Color Designation	White (WH)	T-Storage (Min)		-40 °C
Correlated Color Temperature (Nom)	3000 K	T-Case Maximum (Nom)		45 °C
Luminous Efficacy (rated) (Nom)	142.86 lm/W	Controls and Dimming		
Color Consistency	<6	Dimmable		No
Color Rendering Index (Nom)	82	Mechanical and Housing		
LLMF At End Of Nominal Lifetime (Nom)	70 %	Product Length		1200 mm
Operating and Electrical				
Input Frequency	50 to 60 Hz			
Power (Rated) (Nom)	14 W			

Approval and Application	
Energy Efficiency Label (EEL)	Not applicable
Energy Saving Product	Yes
Approbation Marks	UL certificate RoHS compliance DLC compliance
Energy Consumption kWh/1000 h	- kWh
Energy Certifications	DLC Standard

Product Data	
Order product name	14T8/48-3000 IF 10/1 ROT

EAN/UPC - Product	046677472689
Order code	468652
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001303304
Net Weight (Piece)	0.230 kg
Model Number	9290013033


Dimensional drawing




TLED 1200mm 120V 14-32W 2000lm 3000K G13

Product	D	D2	A1	A2	A3
14T8/48-3000 IF 10/1 ROT	25.68 mm	26.3 mm	1198 mm	1205 mm	1212 mm

Photometric data




LEDtube 1200mm 15W G13 T8 830 2000lm




LEDtube 1200mm 14-32W G13 830 2000lm

Photometric data




LEDtube 1200mm 14-32W G13 830 2000lm

Lifetime



LEDtube HF 1500mm 26W G5 T5



LEDtube 1200mm 14-32W G13

