

8013



Product features and benefits

- Dependable quality
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Technical data

General product information

Product Number	76311
Product Name	8013 6V 100/CS 1/SKU
Ordering Abbreviation	8013
Brand Name	OSRAM
General Description	10 watt, nonhalogen, low voltage
Application	Projector
Product Remark	– h (Operating Position) = Vertical, base up

Electrical data

Nominal Wattage	10 W
Nominal Voltage	6 V
Type of Current	AC

Light technical data

Color Rendering Index	100
Average Rated Life	200 h


Physical attributes

Base	BA15d Double Contact Bayonet
Bulb Shape	P25
Maximum Overall Length (in)	1.794 in
Maximum Overall Length (mm)	46 mm
Length l (in)	1.794 in
Length l (mm)	46 mm
Length l max. (in)	1.794 in
Length l max. (mm)	46 mm
Diameter d (in)	0.984 in
Diameter d (mm)	25.00 mm
Distance a (in)	1.170 in
Distance a (mm)	30 mm
Filament Dimensions Length (in)	0.0350 in
Filament Dimensions Length (mm)	0.9 mm
Filament Dimensions Width (in)	0.066 in
Filament Dimensions Width (mm)	1.7 mm

Additional product data

Product datasheet

Operating Position	h 105
Class	C (gas)



h 105

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
76311	0046135763113	Folding box (SKU)	1		
76311	10046135763110	Shipping box (Case)	100	11.2 in x 5.9 in x 5.3 in	5.6 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.