



LED 120-277V Lamps

Product Specifications

TCP's LED Universal Voltage 120-277V lamps are now available in A-lamps, BR30s, and PAR38s.

Reasons to choose LED 120-277V from TCP

- Long life: 25,000 hours minimizes replacement and maintenance costs
- Up to 85% less energy than halogen alternatives
- Excellent color consistency and CRI
- PAR38 lamps are UL approved for wet locations
- Highly durable plastic

Ideal Applications

- Commercial
- Industrial
- Docks
- Warehouses
- Work sites
- Outdoor flood

Specifications:

Input Line Voltage 120-277 VAC
Input Line Frequency..... 50/60HZ
Lamp Life (Rated) 25,000 hours
Minimum Starting Temp -22F/-30C

Maximum Operating Temp.....45°C
CRI..... 80
Warranty..... 5 years



A19
60W



A21
100W



A23
125W



BR30
65W



BR30
100W



PAR38
120W



LED 120-277V Lamps

Specifications:

ITEM #	DESCRIPTION	ENERGY STAR	CBCP	WATTS	LIFE	REPLACEMENT LUMENS	BEAM ANGLE	CCT	CRI	MOL (inches)	DIA (inches)	BASE	MASTER PACK
18W LED A23 Non Dimmable													
L125A23N25UNV27K	LED 125W A23 UNV 2700K	YES	-	18	25000	125	2000	OMNI	2700	80	5.8	3.1	E26 12
L125A23N25UNV30K	LED 125W A23 UNV 3000K	NO	-	18	25000	125	2000	OMNI	3000	80	5.8	3.1	E26 12
L125A23N25UNV40K	LED 125W A23 UNV 4000K	NO	-	18	25000	125	2100	OMNI	4000	80	5.8	3.1	E26 12
L125A23N25UNV50K	LED 125W A23 UNV 5000K	YES	-	18	25000	125	2200	OMNI	5000	80	5.8	3.1	E26 12
14W LED A21 Non Dimmable													
L100A21N25UNV27K	LED 14W A21 UNV 2700K	YES	-	14	25000	100	1600	OMNI	2700	80	5.2	2.8	E26 12
L100A21N25UNV30K	LED 14W A21 UNV 3000K	YES	-	14	25000	100	1625	OMNI	3000	80	5.2	2.8	E26 12
L100A21N25UNV40K	LED 14W A21 UNV 4000K	YES	-	14	25000	100	1650	OMNI	4000	80	5.2	2.8	E26 12
L100A21N25UNV50K	LED 14W A21 UNV 5000K	YES	-	14	25000	100	1650	OMNI	5000	80	5.2	2.8	E26 12
7.5W LED A19 Non Dimmable													
L60A19N25UNV27K	LED 60W A19 UNV 2700K	YES	-	7.5	25000	60	800	OMNI	2700	80	4.1	2.4	E26 12
L60A19N25UNV30K	LED 60W A19 UNV 3000K	YES	-	7.5	25000	60	800	OMNI	3000	80	4.1	2.4	E26 12
L60A19N25UNV40K	LED 60W A19 UNV 4000K	YES	-	7.5	25000	60	850	OMNI	4000	80	4.1	2.4	E26 12
L60A19N25UNV50K	LED 60W A19 UNV 5000K	YES	-	7.5	25000	60	875	OMNI	5000	80	4.1	2.4	E26 12
9.5W LED BR30 Non Dimmable													
L65BR30N25UNV27K	LED 65W BR30 UNV 2700K	YES	-	9.5	25000	65	900	110°	2700	80	5.2	3.8	E26 12
L65BR30N25UNV30K	LED 65W BR30 UNV 3000K	YES	-	9.5	25000	65	900	110°	3000	80	5.2	3.8	E26 12
L65BR30N25UNV40K	LED 65W BR30 UNV 4000K	YES	-	9.5	25000	65	950	110°	4000	80	5.2	3.8	E26 12
L65BR30N25UNV50K	LED 65W BR30 UNV 5000K	YES	-	9.5	25000	65	1000	110°	5000	80	5.2	3.8	E26 12
13W LED BR30 Non Dimmable													
L100BR30N25UNV27K	LED 100W BR30 UNV 2700K	YES	-	13	25000	100	1400	110°	2700	80	5.3	3.6	E26 12
L100BR30N25UNV30K	LED 100W BR30 UNV 3000K	YES	-	13	25000	100	1400	110°	3000	80	5.3	3.6	E26 12
L100BR30N25UNV40K	LED 100W BR30 UNV 4000K	YES	-	13	25000	100	1450	110°	4000	80	5.3	3.6	E26 12
L100BR30N25UNV50K	LED 100W BR30 UNV 5000K	YES	-	13	25000	100	1500	110°	5000	80	5.3	3.6	E26 12
12.5W LED PAR38 Non Dimmable													
L100P38N25UNV27KFL	LED 90W P38 UNV 2700K Fld	YES	2630	12.5	25000	90	1100	40°	2700	80	5.2	4.8	E26 12
L100P38N25UNV30KFL	LED 90W P38 UNV 3000K Fld	YES	2613	12.5	25000	90	1100	40°	3000	80	5.2	4.8	E26 12
L100P38N25UNV40KFL	LED 90W P38 UNV 4000K Fld	YES	2532	12.5	25000	90	1150	40°	4000	80	5.2	4.8	E26 12
L100P38N25UNV50KFL	LED 90W P38 UNV 5000K Fld	YES	2641	12.5	25000	90	1200	40°	5000	80	5.2	4.8	E26 12
L100P38N25UNV27KNFL	LED 90W P38 UNV 2700K Nar Fld	YES	6245	12.5	25000	90	1100	25°	2700	80	5.2	4.8	E26 12
L100P38N25UNV30KNFL	LED 90W P38 UNV 3000K Nar Fld	YES	6334	12.5	25000	90	1100	25°	3000	80	5.2	4.8	E26 12
L100P38N25UNV40KNFL	LED 90W P38 UNV 4000K Nar Fld	YES	6412	12.5	25000	90	1150	25°	4000	80	5.2	4.8	E26 12
L100P38N25UNV50KNFL	LED 90W P38 UNV 5000K Nar Fld	YES	6572	12.5	25000	90	1200	25°	5000	80	5.2	4.8	E26 12