



LED A-Lamps

Omni-directional
All-purpose
3-way



40W NON DIMMABLE 40W DIMMABLE 60 & 75W NON DIMMABLE 60 & 75W DIMMABLE 60 GU24 DIMMABLE

100W NON DIMMABLE 100W DIMMABLE 100W GU24 DIMMABLE 40/60/100W 3-WAY 60W DIMMABLE WET LOCATION

TCP's LED A-lamps provide the lighting you need at a cost you will love. Advanced factory techniques and rigorous testing ensure each lamp is perfect from day one. Install a LED A-lamp wherever you would a traditional lamp and see the improvement.

Reasons to choose the LED A-Lamps from TCP

- Up to 85% less energy than halogen alternatives for instant energy savings
- Long life minimizes replacement and maintenance costs
- Very low heat generation, perfect for sensitive display lighting such as galleries
- UL approved for damp locations, can be used in covered indoor and outdoor fixtures
- Excellent color consistency and CRI enhances colors of focal point while maintaining uniformity throughout lighting installation from lamp to lamp
- Durable polycarbonate material for shatterproof composition lowering the risk of injury and breakage
- ANSI construction compliant fits all A-lamp installations
- Dims to $\leq 10\%$ of full light level when applicable

Ideal Applications

- General lighting
- Table lamps
- Floor lamps
- Sconces
- Ceiling fixtures

Specifications:

Voltage 120 VAC
 Input Line Frequency..... 50/60HZ
 Lamp Life (Rated) 10,000/15,000/25,000 hours
 Minimum Starting Temp -30°C
 Maximum Operating Temp..... 40°C

CRI 80

Suitable for use in totally enclosed fixtures (Vapor tight or jelly jar applications may reduce life)

Do not use more than 2 bulbs in an enclosed fixture. If fixture is manufactured for incandescent bulbs, use no higher than the LED equivalent wattage, as shown on this spec sheet.

Specifications:

ITEM #	DESCRIPTION	ENERGY STAR	VOLTAGE	WATTS	INCANDESCENT WATTS	LPW	LUMENS	COLOR	HOURS	CRI	MOL (IN.)	DIA (IN.)	BASE	WARRANTY YEARS	CASE QTY
6W A19 A-Lamp – Non-Dimmable • 15,000 Hours															
L6A19N1527K	LED 6W A19 ND 2700K	★	120	6	40	80	480	2700K	15,000	80	4.0	2.2	E26	3	12
L6A19N1530K	LED 6W A19 ND 3000K	★	120	6	40	80	480	3000K	15,000	80	4.0	2.2	E26	3	12
L6A19N1541K	LED 6W A19 ND 4100K	★	120	6	40	80	480	4100K	15,000	80	4.0	2.2	E26	3	12
L6A19N1550K	LED 6W A19 ND 5000K	★	120	6	40	80	480	5000K	15,000	80	4.0	2.2	E26	3	12
6W A19 A-Lamp – Dimmable • 25,000 Hours															
L40A19D2524K	LED 6W A19 DIM 2400K		120	6	40	62.5	375	2400K	25,000	80	4.1	2.4	E26	5	12
L40A19D2527K	LED 6W A19 DIM 2700K	★	120	6	40	80	480	2700K	25,000	80	4.1	2.4	E26	5	12
L40A19D2530K	LED 6W A19 DIM 3000K	★	120	6	40	80	480	3000K	25,000	80	4.1	2.4	E26	5	12
L40A19D2541K	LED 6W A19 DIM 4100K	★	120	6	40	83.3	500	4100K	25,000	80	4.1	2.4	E26	5	12
L40A19D2550K	LED 6W A19 DIM 5000K	★	120	6	40	87.5	525	5000K	25,000	80	4.1	2.4	E26	5	12
9.5W A19 A-Lamp – Non-Dimmable • 10,000 Hours															
I9A19N1027K4	LED 9.5W A19 ND 2700K 4 PACK		120	9.5	60	84.2	800	2700K	10,000	80	4.3	2.4	E26	1	12
I9A19N1030K4	LED 9.5W A19 ND 3000K 4 PACK		120	9.5	60	84.2	800	3000K	10,000	80	4.3	2.4	E26	1	12
I9A19N1041K4	LED 9.5W A19 ND 4100K 4 PACK		120	9.5	60	84.2	800	4100K	10,000	80	4.3	2.4	E26	1	12
9W A19 A-Lamp – Non-Dimmable • 15,000 Hours															
L60A19N1527K	LED 9W A19 ND 2700K	★	120	9	60	88.9	800	2700K	15,000	80	4.3	2.4	E26	3	12
L60A19N1530K	LED 9W A19 ND 3000K	★	120	9	60	88.9	800	3000K	15,000	80	4.3	2.4	E26	3	12
L60A19N1541K	LED 9W A19 ND 4100K	★	120	9	60	94.4	850	4100K	15,000	80	4.3	2.4	E26	3	12
L60A19N1550K	LED 9W A19 ND 5000K	★	120	9	60	94.4	850	5000K	15,000	80	4.3	2.4	E26	3	12
9W A19 A-Lamp – Dimmable • 15,000 Hours															
I9A19D1527K	LED 9W A19 DIM 2700K	★	120	9	60	88.9	800	2700K	15,000	80	4.3	2.4	E26	3	12
I9A19D1527K24	LED 9W A19 DIM 2700K 24 PACK	★	120	9	60	88.9	800	2700K	15,000	80	4.3	2.4	E26	3	=
I9A19D1530K	LED 9W A19 DIM 3000K	★	120	9	60	88.9	800	3000K	15,000	80	4.3	2.4	E26	3	12
I9A19D1541K	LED 9W A19 DIM 4100K	★	120	9	60	91.7	825	4100K	15,000	80	4.3	2.4	E26	3	12
I9A19D1550K	LED 9W A19 DIM 5000K	★	120	9	60	91.7	825	5000K	15,000	80	4.3	2.4	E26	3	12
9W A19 A-Lamp – Dimmable • 25,000 Hours															
I9A19D2524K	LED 9W A19 DIM 2400K		120	9	60	77.7	700	2400K	25,000	80	4.3	2.4	E26	5	12
I9A19D2527K	LED 9W A19 DIM 2700K	★	120	9	60	88.9	800	2700K	25,000	80	4.3	2.4	E26	5	12
I9A19D2530K	LED 9W A19 DIM 3000K	★	120	9	60	88.9	800	3000K	25,000	80	4.3	2.4	E26	5	12
I9A19D2535K	LED 9W A19 DIM 3500K		120	9	60	88.9	800	3500K	25,000	80	4.3	2.4	E26	5	12
I9A19D2541K	LED 9W A19 DIM 4100K	★	120	9	60	91.7	825	4100K	25,000	80	4.3	2.4	E26	5	12
I9A19D2550K	LED 9W A19 DIM 5000K	★	120	9	60	91.7	825	5000K	25,000	80	4.3	2.4	E26	5	12
9W A19 A-Lamp – Allusion Dimmable • 25,000 Hours															
I9A19DA	LED 9W A19 2000K - 2700K ALLUSION		120	9	60	72.2	650	2000K-2700K	25,000	80	4.6	2.4	E26	5	12
9.5W A19 Omni-Directional A-Lamp GU24 – Dimmable • 25,000 Hours															
I9A19GUD0D27K	LED 9.5W A19 DIM OMNI 27K GU24	★	120	9.5	60	84.2	800	2700K	25,000	80	4.4	2.4	GU24	5	12
I9A19GUD0D30K	LED 9.5W A19 DIM OMNI 30K GU24	★	120	9.5	60	89.5	850	3000K	25,000	80	4.4	2.4	GU24	5	12
I9A19GUD0D41K	LED 9.5W A19 DIM OMNI 41K GU24	★	120	9.5	60	89.5	850	4100K	25,000	80	4.4	2.4	GU24	5	12
11W A19 A-Lamp – Non-Dimmable • 15,000 Hours															
L11A19N1527K	LED 11W A19 ND 2700K	★	120	11	75	100	1100	2700K	15,000	80	4.4	2.4	E26	3	12
L11A19N1530K	LED 11W A19 ND 3000K	★	120	11	75	104.5	1150	3000K	15,000	80	4.4	2.4	E26	3	12
L11A19N1541K	LED 11W A19 ND 4100K	★	120	11	75	109	1200	4100K	15,000	80	4.4	2.4	E26	3	12
L11A19N1550K	LED 11W A19 ND 5000K	★	120	11	75	109	1200	5000K	15,000	80	4.4	2.4	E26	3	12

ITEM #	DESCRIPTION	ENERGY STAR	VOLTAGE	WATTS	INCANDESCENT WATTS	LPW	LUMENS	COLOR	HOURS	CRI	MOL (IN.)	DIA (IN.)	BASE	WARRANTY YEARS	CASE QTY
11.5W/13.5W A19 A-Lamp – Dimmable • 25,000 Hours															
L11A19D2527K	LED 13.5W A19 DIM 2700K	★	120	13.5	75	81.5	1100	2700K	25,000	80	4.4	2.4	E26	5	12
L11A19D2530K	LED 11.5W A19 DIM 3000K	★	120	11.5	75	81.5	1100	3000K	25,000	80	4.4	2.4	E26	5	12
L11A19D2541K	LED 11.5W A19 DIM 4100K	★	120	11.5	75	81.5	1100	4100K	25,000	80	4.4	2.4	E26	5	12
L11A19D2550K	LED 13.5W A19 DIM 5000K	★	120	13.5	75	81.5	1100	5000K	25,000	80	4.4	2.4	E26	5	12
14W A19 A-Lamp – Non-Dimmable • 10,000 Hours															
L16A19N1027K4	LED 14W A19 ND 2700K 4PK		120	14	100	107.1	1500	2700K	10,000	80	4.7	2.6	E26	1	12
L16A19N1041K4	LED 14W A19 ND 4100K 4PK		120	14	100	107.1	1500	4100K	10,000	80	4.7	2.6	E26	1	12
15.5W A19 A-Lamp – Non-Dimmable • 15,000 Hours															
L16A19N1527K	LED 15.5W A19 ND 2700K	★	120	15.5	100	103.2	1600	2700K	15,000	80	4.7	2.6	E26	3	12
L16A19N1530K	LED 15.5W A19 ND 3000K	★	120	15.5	100	106.5	1650	3000K	15,000	80	4.7	2.6	E26	3	12
L16A19N1541K	LED 15.5W A19 ND 4100K	★	120	15.5	100	109.7	1700	4100K	15,000	80	4.7	2.6	E26	3	12
L16A19N1550K	LED 15.5W A19 ND 5000K	★	120	15.5	100	112.9	1750	5000K	15,000	80	4.7	2.6	E26	3	12
15W A19 A-Lamp – Dimmable • 15,000 Hours															
L15A21D1527K	LED 15W A19 DIM 2700K	★	120	15	100	106.7	1600	2700K	15,000	80	4.7	2.6	E26	3	12
L15A21D1530K	LED 15W A19 DIM 3000K	★	120	15	100	110.0	1650	3000K	15,000	80	4.7	2.6	E26	3	12
L15A21D1541K	LED 15W A19 DIM 4100K	★	120	15	100	113.3	1700	4100K	15,000	80	4.7	2.6	E26	3	12
L15A21D1550K	LED 15W A19 DIM 5000K	★	120	15	100	116.7	1750	5000K	15,000	80	4.7	2.6	E26	3	12
15W A19 A-Lamp – Dimmable • 25,000 Hours															
L15A19D2527K	LED 15W A19 DIM 2700K	★	120	15	100	106.7	1600	2700K	25,000	80	4.7	2.6	E26	5	12
L15A19D2530K	LED 15W A19 DIM 3000K	★	120	15	100	106.7	1600	3000K	25,000	80	4.7	2.6	E26	5	=
L15A19D2541K	LED 15W A19 DIM 4100K	★	120	15	100	106.7	1600	4100K	25,000	80	4.7	2.6	E26	5	12
L15A19D2550K	LED 15W A19 DIM 5000K	★	120	15	100	106.7	1600	5000K	25,000	80	4.7	2.6	E26	5	12
14W A21 A-Lamp GU24 – Dimmable • 25,000 Hours															
L14A21GUD2527K	LED 14W A21 DIM 2700K GU24	★	120	14	100	114.3	1600	2700K	25,000	80	5.2	2.4	GU24	5	12
L14A21GUD2530K	LED 14W A21 DIM 3000K GU24	★	120	14	100	114.3	1600	3000K	25,000	80	5.2	2.4	GU24	5	12
L14A21GUD2541K	LED 14W A21 DIM 4100K GU24	★	120	14	100	121.4	1700	4100K	25,000	80	5.2	2.4	GU24	5	12
L14A21GUD2550K	LED 14W A21 DIM 5000K GU24	★	120	14	100	121.4	1700	5000K	25,000	80	5.2	2.4	GU24	5	12
4/8/16W A21 3-Way A-Lamp • 25,000 Hour															
LED16A21D3WAY27K	LED 16W A21 2700K 3WAY	★	120	4/8/16	40/60/100	120/100/100	480/800/1600	2700K	25,000	80	4.9	2.6	E26	5	12
LED16A21D3WAY30K	LED 16W A21 3000K 3WAY	★	120	4/8/16	40/60/100	120/100/100	480/800/1600	3000K	25,000	80	4.9	2.6	E26	5	12
LED16A21D3WAY41K	LED 16W A21 4100K 3WAY	★	120	4/8/16	40/60/100	120/100/100	480/800/1600	4100K	25,000	80	4.9	2.6	E26	5	12
LED16A21D3WAY50K	LED 16W A21 5000K 3WAY	★	120	4/8/16	40/60/100	120/100/100	480/800/1600	5000K	25,000	80	4.9	2.6	E26	5	12
9.5W A19 Omni-Directional Wet Location A-Lamp – Dimmable • 15,000 Hours															
LED10A19DOD27KW	LED 9.5W A19 DIM OMNI 27K WET	★	120	9.5	60	84.2	800	2700K	25,000	80	4.6	2.5	E26	5	12
LED10A19DOD30KW	LED 9.5W A19 DIM OMNI 30K WET	★	120	9.5	60	86.8	825	3000K	25,000	80	4.6	2.5	E26	5	12
LED10A19DOD41KW	LED 9.5W A19 DIM OMNI 41K WET	★	120	9.5	60	89.5	850	4100K	25,000	80	4.6	2.5	E26	5	12
LED10A19DOD50KW	LED 9.5W A19 DIM OMNI 50K WET	★	120	9.5	60	89.5	850	5000K	25,000	80	4.6	2.5	E26	5	12

For the most up-to-date specs, please visit www.tcp.com

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcp.com

©TCP JUN 2020/WF195102



1 YEAR WARRANTY*
10,000 HOUR LAMPS

3 YEAR WARRANTY
*Based on 12 hours use per day

5 YEAR WARRANTY
*Based on 12 hours use per day

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 20 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcp.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516