



LED Recessed Retrofits

Product Specifications



TCP's Dimmable Retrofit Kits are the perfect choice for new construction and retrofit opportunities when a sleek, integrated look is preferred.

Reasons to choose the LED Recessed Retrofits from TCP

- 35,000 hour life minimizes replacement and maintenance costs
- Very low heat generation is perfect for sensitive display lighting
- Excellent color consistency and CRI enhances colors of focal point while maintaining uniformity throughout lighting installation
- Mounts directly to recessed can (4 or 5-6 inch) for easy installation and integrated trim, including pigtail and spring clips
- Shatter resistant
- Smooth, uniform dimming from 100 - 5%

Ideal Applications

- Commercial
- Healthcare
- Residential
- Retail
- Industrial

Specifications:

Color Temperatures 2700K, 3000K, 4100K, 5000K
Wattage options 12W, 11W, 10W, 9.5W, 9W
Input Line Voltage 120 VAC
Input Line Frequency 50/60HZ
Lamp Life (rated) 35,000 hours
Minimum Starting Temp -22F/-30C

Maximum Operating Temp 40°C
CRI 80, 90
IC-rated for direct contact with insulation
UL approved for damp location (indoor only)—outdoor environment may cause yellowing of the white trim. This is not covered by warranty.

Specifications:



4 inch
Recessed Retrofit



5/6 inch
Recessed Retrofit



4 inch HiCRI
Recessed Retrofit



5/6 inch HiCRI
Recessed Retrofit



ITEM #	DESCRIPTION	ENERGY STAR	V2.2	VOLTAGE	LED WATTS	REPLACE- MENT	LUMENS	LPW	CRI	COLOR TEMP	MOL (inches)	DIA (inches)	CASE QTY
5/6" Recessed Retrofits													
120 Watt Replacement • 35,000 Hour													
LED14DR5627K	LED 5/6" 12W DIM 120W EQ - 2700K	★		120V	12	120	1250	104.2	80	2700K	3.0	7.4	6
LED14DR5630K	LED 5/6" 12W DIM 120W EQ - 3000K	★		120V	12	120	1300	108.3	80	3000K	3.0	7.4	6
LED14DR5641K	LED 5/6" 12W DIM 120W EQ - 4100K	★		120V	12	120	1300	108.3	80	4100K	3.0	7.4	6
LED14DR5650K	LED 5/6" 12W DIM 120W EQ - 5000K	★		120V	12	120	1350	112.5	80	5000K	3.0	7.4	6
75 Watt Replacement • 35,000 Hour													
LED11DR5627K	LED 5/6" 9.5W DIM 75W EQ - 2700K	★		120V	9.5	75	850	89.5	80	2700K	3.0	7.4	6
LED11DR5630K	LED 5/6" 9.5W DIM 75W EQ - 3000K	★		120V	9.5	75	850	89.5	80	3000K	3.0	7.4	6
LED11DR5641K	LED 5/6" 9.5W DIM 75W EQ - 4100K	★		120V	9.5	75	875	92.1	80	4100K	3.0	7.4	6
LED11DR5650K	LED 5/6" 9.5W DIM 75W EQ - 5000K	★		120V	9.5	75	900	94.7	80	5000K	3.0	7.4	6
HiCRI • 65 Watt Replacement • 35,000 Hour													
L11DR56D3527K95*	LED 5/6" 11W HiCRI DIM 65W EQ - 2700K	★		120V	11	65	700	63.6	90	2700K	3.125	7.4	6
L11DR56D3530K95*	LED 5/6" 11W HiCRI DIM 65W EQ - 3000K	★		120V	11	65	750	68.2	90	3000K	3.125	7.4	6
4" Recessed Retrofits													
75 Watt Replacement • 35,000 Hour													
LED10DR427K	LED 4" 10W DIM 75W EQ - 2700K	★		120V	10	75	750	75.0	80	2700K	3.0	5.0	6
LED10DR430K	LED 4" 10W DIM 75W EQ - 3000K	★		120V	10	75	750	75.0	80	3000K	3.0	5.0	6
LED10DR441K	LED 4" 10W DIM 75W EQ - 4100K	★		120V	10	75	800	80.0	80	4100K	3.0	5.0	6
LED10DR450K	LED 4" 10W DIM 75W EQ - 5000K	★		120V	10	75	800	80.0	80	5000K	3.0	5.0	6
HiCRI • 50 Watt Replacement • 35,000 Hour													
L9DR4D3527K95*	LED 4" 9W HiCRI DIM 50W EQ - 2700K	★		120V	9	50	550	61.1	90	2700K	3.0	5.2	6
L9DR4D3530K95*	LED 4" 9W HiCRI DIM 50W EQ - 3000K	★		120V	9	50	600	66.7	90	3000K	3.0	5.2	6

* All Plastic Body