



LED Classic Filament T-Lamps

Product Specifications



The filament style LED T-lamps from TCP provide beauty and versatility as traditional T-lamps with the savings of LED. Exclusive LED technology provides unmatched longevity and perfect 5-100% dimming.

Reasons to choose the LED LAMP from TCP

- **Smooth, Uniform Dimming from 5 - 100%**
- Energy efficient – Up to 85% less energy than halogen lamps
- Very low heat generation – Minimizes replacement and maintenance costs
- 15,000 hours rated life
- UL approved for damp and enclosed locations so lamp can be used outdoors when protected from elements. Withstands humidity indoors/outdoors
- Unique filament LED configuration provides a uniform color output
- ANSI construction compliant fits most general applications

Ideal Applications

- Accent Lighting
- Decorative Lighting
- General Lighting

Specifications:

Color Temperature options..... 2200K, 2400K, 2700K,
3000K, 4000K, 5000K
Input Line Voltage 120 VAC
Input Line Frequency..... 50/60HZ
Lamp Life (Rated) 15,000 hours

Minimum Starting Temp -30°C
Maximum Operating Temp..... 40°C
CRI..... >80
Base E12/E26



LED Classic Filament T-Lamps

Specifications:



ITEM #	DESCRIPTION	LED WATTS	INCAND. WATTS	LUMENS	FILAMENTS	CRI	COLOR TEMP	GLASS TYPE	MOL (inches)	DIA (inches)	BASE
T6											
25 Watt Replacements • Dimmable • E12 Base • 15,000 Hour											
FT0603D2522E12SB	T6 25W 2200K E12 SANDBLAST	3.0	25	200	2	>80	2200K	SandBlast	3.3	0.8	E12
FT0603D2524E12SB	T6 25W 2400K E12 SANDBLAST	3.0	25	200	2	>80	2400K	SandBlast	3.3	0.8	E12
FT0603D2527E12C	T6 25W 2700K E12 CLEAR	3.0	25	250	2	>80	2700K	Clear	3.3	0.8	E12
FT0603D2527E12W	T6 25W 2700K E12 FROST	3.0	25	250	2	>80	2700K	Frosted	3.3	0.8	E12
T10											
25 Watt Replacements • Dimmable • E26 Base • 15,000 Hour											
FT1005D2524SB	T10 25W 2400K E26 SANDBLAST	3.5	25	250	2	>80	2400K	SandBlast	5.4	1.2	E26
FT1005D2527EC	T10 25W 2700K E26 CLEAR	3.5	25	250	2	>80	2700K	Clear	5.4	1.2	E26
FT1005D2527EW	T10 25W 2700K E26 FROST	3.5	25	250	2	>80	2700K	Frosted	5.4	1.2	E26
FT1005D2550EC	T10 25W 5000K E26 CLEAR	3.5	25	250	2	>80	5000K	Clear	5.4	1.2	E26
FT1005D2550EW	T10 25W 5000K E26 FROST	3.5	25	250	2	>80	5000K	Frosted	5.4	1.2	E26
FT1007D2522SB	T10 25W 2200K E26 SANDBLAST	3.0	25	250	1	>80	2200K	SandBlast	7.0	1.2	E26
FT1007D2524SB	T10 25W 2400K E26 SANDBLAST	3.0	25	250	1	>80	2400K	SandBlast	7.0	1.2	E26
FT1007D2527C	T10 25W 2700K E26 CLEAR	3.0	25	250	1	>80	2700K	Clear	7.0	1.2	E26
40 Watt Replacements • Dimmable • E26 Base • 15,000 Hour											
FT1005D4027EC	T10 40W 2700K E26 CLEAR	5.0	40	450	4	>80	2700K	Clear	5.4	1.2	E26
FT1005D4027EW	T10 40W 2700K E26 FROST	5.0	40	450	4	>80	2700K	Frosted	5.4	1.2	E26
FT1005D4030EW	T10 40W 3000K E26 FROST	5.0	40	450	4	>80	3000K	Frosted	5.4	1.2	E26
FT1005D4040EW	T10 40W 4000K E26 FROST	5.0	40	450	4	>80	4000K	Frosted	5.4	1.2	E26
FT1005D4050EC	T10 40W 5000K E26 CLEAR	5.0	40	450	4	>80	5000K	Clear	5.4	1.2	E26
FT1005D4050EW	T10 40W 5000K E26 FROST	5.0	40	450	4	>80	5000K	Frosted	5.4	1.2	E26
T25											
25 Watt Replacements • Dimmable • E12 Base • 15,000 Hour											
FT2503D2527E12C	T25 25W 2700K E12 CLEAR	3.5	25	250	4	>80	2700K	Clear	3.6	1.0	E12
T30											
60 Watt Replacements • Dimmable • E26 Base • 15,000 Hour											
FT3014D6022SB	T30 60W 2200K E26 SANDBLAST	8.0	60	800	1	>80	2200K	SandBlast	14.0	1.2	E26
FT3014D6024SB	T30 60W 2400K E26 SANDBLAST	8.0	60	800	1	>80	2400K	SandBlast	14.0	1.2	E26
FT3014D6027SB	T30 60W 2700K E26 SANDBLAST	8.0	60	800	1	>80	2700K	SandBlast	14.0	1.2	E26
FT3014D6027EC	T30 60W 2700K E26 CLEAR	8.0	60	800	1	>80	2700K	Clear	14.0	1.2	E26

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcp.com

©TCP AUG 2020/WF217013



RoHS
COMPLIANT

3 YEAR
WARRANTY

*Based on 12 hours
use per day