

EPT



Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	58782
Product Name	EPT 11V 24/CS 1/SKU
Ordering Abbreviation	EPT
Brand Name	OSRAM
General Description	42 watt, tungsten halogen, low to medium voltage with reflector
Application	Projector - Fiber-Optics

Electrical data

Nominal Wattage	42 W
Nominal Voltage	10.8 V
Type of Current	AC

Light technical data

Beam Angle (degree)	35V x 34H deg
Color Temperature	2900 K
Color Rendering Index	100
Average Rated Life	8000 h

Physical attributes

Base	GX5.3 Bipin
Bulb Shape	MR16
Maximum Overall Length (in)	1.689 in
Maximum Overall Length (mm)	43.3 mm
Length l (in)	1.486 in
Length l (mm)	38.1 mm
Length l max. (in)	1.486 in
Length l max. (mm)	38.1 mm
Diameter d (in)	2.008 in
Diameter d (mm)	51.00 mm
Filament	C-6
Reflector Coating	WHITE

Additional product data

Operating Position	Any
Total surface inside 1: appearance (cold)	Clear

Product datasheet

Class	C (gas)
Lamp Type	MR16

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
58782	0046135587825	Folding box (SKU)	1		
58782	10046135587822	Shipping box (Case)	24	7.8 in x 6 in x 5.5 in	2 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.