

6.6A/200T4Q/2PPF/58750/EZL/DL



Product features and benefits

- Low maintenance costs due to long lamp life
- Reliable and consistent light output enhances visibility over the life of the lamp
- FAA approved in conjunction with many OEM fixtures
- Durable construction provides resistance to the effects of vibration
- Broad product portfolio for runway, taxiway, and approach lighting
- IR radiation provides guidance in low visibility conditions
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free

Areas of application

- Airfield Lighting

Technical data

General product information

Product Number	58851
Product Name	6.6A200T4Q2PPF58750EZLDL 12/CS 1/SKU
Ordering Abbreviation	6.6A/200T4Q/2PPF/58750/EZL/DL
Brand Name	OSRAM
General Description	200 WATT, TUNGSTEN HALOGEN, CURRENT CONTROLLED, SINGLED-END, BI-PIN,AIRFIELD LONG LIFE
Application	Airfield/Airport
Product Remark	– This lamp type is twice the life of the ANSI standard version.

Electrical data

Nominal Wattage	200 W
Current (A)	6.6 A
Type of Current	AC

Light technical data

Luminous Flux	5200 lm
Light Center Length - LCL (in)	1.54 in
Light Center Length - LCL (mm)	39.1 mm
Color Temperature	3100 K
Color Rendering Index	100
Average Rated Life	1300 h

Physical attributes

Base	GY9.5 BIPIN
Bulb Shape	T13
Maximum Overall Length (in)	2.56 in
Maximum Overall Length (mm)	65 mm
Diameter d (in)	0.512 in
Diameter d (mm)	13.00 mm
Filament	CC-6
Filament Dimensions Length (in)	0.1490 in
Filament Dimensions Length (mm)	3.8 mm
Filament Dimensions Width (in)	0.216 in
Filament Dimensions Width (mm)	5.5 mm

Product datasheet

Additional product data

Operating Position	Any
Class	C (gas)
Lamp Type	SINGLE ENDED

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
58851	4008321100160	Folding box (SKU)	1	1.7 in x 1.7 in x 4.4 in	0.1 lb
58851	10046135588515	Shipping box (Case)	12	7.1 in x 5.5 in x 5 in	0.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.